

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Commercial Product Name : DERV
Chemical name of the substance : DERV
Specific use(s) : Fuel
Company : Jones Oil
407-410, The Capel Building, Mary's Abbey, Dublin.
01 855 0570
online@jonesoil.ie
www.jonesoil.ie

Emergency telephone number : +353 1 809 2166

2. HAZARDS IDENTIFICATION

Classification : The product is classified as dangerous in accordance with Directive 67/548/EEC.



Xn : Harmful



N : Dangerous for the environment

Most important hazards : R20 - Harmful by inhalation.
R38 - Irritating to skin.
R65 - Harmful: may cause lung damage if swallowed.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLP-Classification : The product is classified as dangerous in accordance with Directive 1272/2008/EEC.



Signal word : Danger

CLP Hazard statements : H226 - Flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H315 - Causes skin irritation.
H332 - Harmful if inhaled.
H411 - Toxic to aquatic life with long lasting effects.

Main symptoms
Inhalation : May cause irritation of respiratory tract.
Effects of breathing high concentrations of vapour may include: headache, nausea, dizziness
Inhalation of high vapour concentrations can cause CNS-depression and narcosis

Issuing Date: 01/10/2010 Revision Date: 01/01/2019 Page 2

- Skin contact : Irritating to skin.
Redness
Repeated exposure may cause skin dryness or cracking.
- Eye contact : May cause eye irritation.
- Ingestion : Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung oedema or pneumonia.
- Environmental properties : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance name	Values (%)	CAS no	EC No	EC Index	Symbol(s)	R-phrase(s)
Distillates (petroleum), hydrotreated middle		64742-46-7	265-148-2	649-221-00-X	Xn	R20, R38, R65

Full text of R-phrases: See section 16.

Substance name	Values (%)	CAS no	EC No	EC Index	CLP pictograms	CLP Hazard statements
Distillates (petroleum), hydrotreated middle		64742-46-7	265-148-2	649-221-00-X	GHS08,GHS07,GHS09	H304,H315, H332,H411

Full text of the H-statements: See section 16.

4. FIRST AID MEASURES

First aid measures

- Inhalation : *May cause irritation of respiratory tract.- Effects of breathing high concentrations of vapour may include: headache, nausea, dizziness- Inhalation of high vapour concentrations can cause CNS-depression and narcosis.*
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep at rest.
- Skin contact : *Irritating to skin.- Redness- Repeated exposure may cause skin dryness or cracking.*
Take off contaminated clothing and shoes immediately.
Wash immediately with lots of water (15 minutes)/shower
Wash off with soap and water.
If a person feels unwell or symptoms of skin irritation appear, consult a physician.
- Eye contact : *May cause eye irritation.*
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If pain persists, call a physician.
- Ingestion : *Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.- Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung oedema or pneumonia.*

Issuing Date: 01/10/2010 Revision Date: 01/01/2019 Page 3

Additional advice : Call a physician immediately.
Do NOT induce vomiting.
Rinse mouth.
Drink plenty of water.
: Never give anything by mouth to an unconscious person.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Fire Hazard : Combustible material
Suitable extinguishing media : Dry chemical
Carbon dioxide (CO₂)
Water spray
Foam
Use water spray to cool unopened containers.
Extinguishing media which shall not be used for safety reasons : High volume water jet
Specific hazards : Temperature above flashpoint: higher fire/explosion hazard
Vapours may form explosive mixtures with air.
Burning produces noxious and toxic fumes.
In case of fire hazardous decomposition products may be produced such as:
Carbon oxides
Sulphur oxides
Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Wear personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Avoid contact with skin and eyes.
Do not breathe vapours or spray mist.
Wear personal protective equipment.
See also section 8.
Environmental precautions : Prevent product from entering drains.
Methods for cleaning up : Remove all sources of ignition.
Take precautionary measures against static discharges.
Ensure adequate ventilation.
Prevent further leakage or spillage if safe to do so.
Dam up.
Soak up with inert absorbent material.
Sweep up and shovel into suitable containers for disposal.
Collect and dispose of waste product at an authorised disposal facility.
Dispose of in accordance with local regulations.
Local authorities should be advised if significant spillages cannot be contained.

Issuing Date: 01/10/2010

Revision Date: 01/01/2019

Page 4

Storage	: Keep containers tightly closed in a dry, cool and well-ventilated place. Store in original container. Keep in a bunded area. Keep away from open flames, hot surfaces and sources of ignition. Do not store near or with any of the incompatible materials listed in section 10. Keep away from food, drink and animal feedingstuffs.
Handling	: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Ensure all equipment is electrically grounded before beginning transfer operations. Do not use pressure to empty drums. Do not smoke. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Wear personal protective equipment. See also section 8. Ensure adequate ventilation. When using do not eat or drink. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not burn, or use a cutting torch on, the empty drum.
Packaging material	: metal containers, glass, Plastic jerrican
Specific use(s)	: Fuel

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protective equipment

Respiratory protection	: In case of insufficient ventilation wear suitable respiratory equipment. respirator with A filter (type A1/A2/A3 Wear a positive-pressure supplied-air respirator. (in case of higher concentration)
Hand protection	: Protective gloves Nitrile rubber Viton (R) EN374 The selection of specific gloves for a specific application and time of use in a working area, should also take into account other factors on the working space, such as (but not limited to): other chemicals that are possibly used, physical requirements (protection against cutting/drilling, skill, thermal protection), and the instructions/specification of the supplier of gloves.
Eye protection	: Safety glasses with side-shields conforming to EN166 Goggles
Skin and body protection	: Overalls, apron and boots recommended.
Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use. Keep working clothes separately.
Engineering measures	: Provide sufficient air exchange and/or exhaust in work rooms.
Environmental exposure controls	: Do not flush into surface water or sanitary sewer system.

Exposure limit(s)

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

Appearance	: Liquid
Colour	: Pale Yellow
Odour	: Petroleum hydrocarbon odour
pH	: not applicable
Boiling point/boiling range	: 180 - 390 °C
Melting point/range	: no data available
Flash point	: > 61°C
Decomposition temperature	: no data available
Autoignition temperature	: 250 °C
Explosive properties	: LEL 0,5 vol% - UEL 7 vol %
Oxidizing properties	: no data available
Evaporation rate	: no data available
Vapour pressure	: < 1 hPa @ 20°C
Vapour density	: > 1
Water solubility	: insoluble
Viscosity	: 1,5 - 5 mm ² /s @ 40°C
Density	: 0,82 - 0,88 g/cm ³ @ 15°C
Partition coefficient: n-octanol/water	: > 3

10. STABILITY AND REACTIVITY

Stability	: Stable under normal conditions.
Hazardous decomposition products	: No decomposition if stored and applied as directed. Burning produces noxious and toxic fumes. Possible decomposition products are: Carbon oxides Sulphur oxides
Incompatible materials	: Strong acids and oxidizing agents
Conditions to avoid	: Heat, flames and sparks. Exposure to sunlight.

11. TOXICOLOGICAL INFORMATION

General Information

Acute toxicity

Inhalation	: May cause irritation of respiratory tract. Effects of breathing high concentrations of vapour may include: headache, nausea, dizziness Inhalation of high vapour concentrations can cause CNS-depression and narcosis.
Skin contact	: Irritating to skin. Redness Repeated exposure may cause skin dryness or cracking.

Issuing Date: 01/10/2010 Revision Date: 01/01/2019 Page 6

Eye contact	:	May cause eye irritation.
Ingestion	:	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung oedema or pneumonia.
Chronic toxicity	:	
Chronic toxicity	:	Repeated exposure may cause skin dryness or cracking.
Sensitisation	:	No sensitization responses were observed.
carcinogenic effects	:	No adverse effects are expected.
Reproductive toxicity	:	No adverse effects are expected.


12. ECOLOGICAL INFORMATION

Ecotoxicity effects	:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Mobility	:	partly soluble
Persistence and degradability	:	Inherently biodegradable.
Bioaccumulation	:	May cause bioaccumulation.
Partition coefficient: n-octanol/water	:	> 3

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products	:	Where possible recycling is preferred to disposal or incineration. Do not burn, or use a cutting torch on, the empty drum. Dispose of in accordance with local regulations. Empty containers should be transported/delivered using a registered waste carrier to local recyclers for disposal.
Contaminated packaging	:	Dispose of in accordance with local regulations.
Additional ecological information	:	Do not flush into surface water or sanitary sewer system.
Codes of waste (2001/573/EC, 75/442/EEC, 91/689/EEC)	:	The following Waste Codes are only suggestions: 13 07 01* - fuel oil and diesel 15 01 10* - packaging containing residues of or contaminated by dangerous substances Waste codes should be assigned by the user based on the application for which the product was used.

14. TRANSPORT INFORMATION

ADR danger labels	:	
ADR/RID	:	
Proper shipping name	:	GAS OIL / DIESEL FUEL / HEATING OIL, LIGHT
UN-No	:	1202
Class	:	3
Packing group	:	III

Issuing Date: 01/10/2010 Revision Date: 01/01/2019 Page 7

ADNR

ADNR class : 3 - Flammable liquids
ADNR classification code : F1
ADNR UN number : 1202

IMDG

Proper shipping name : GAS OIL / DIESEL FUEL / HEATING OIL, LIGHT
UN-No : 1202
Class : 3
Packing group : III
EmS : F-E; S-E
IMDG Limited Quantities : 5 L

ICAO/IATA

Proper shipping name : GAS OIL / DIESEL FUEL / HEATING OIL, LIGHT
UN-No : 1202
Class : 3
UN packing group : III

Other information (transport) : Tunnel restriction code D/E

15. REGULATORY INFORMATION

Classification : The product is classified as dangerous in accordance with Directive 67/548/EEC.

Commercial Product Name : DERV

Chemical name of the substance : DERV

EC No : 265-148-2

CAS no : 64742-46-7

Symbol(s):




Xn N

Xn - Harmful
N - Dangerous for the environment

R-phrase(s) : R20 - Harmful by inhalation.
R38 - Irritating to skin.
R65 - Harmful: may cause lung damage if swallowed.
R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases : S36/37 - Wear suitable protective clothing and gloves
S61 - Avoid release to the environment. Refer to special instructions/Safety data sheets.
S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Issuing Date: 01/10/2010 Revision Date: 01/01/2019 Page 8

CLP-Classification	:	The product is classified as dangerous in accordance with Directive 1272/2008/EEC.
CLP pictograms	:	
Signal word	:	Danger
CLP Hazard statements	:	H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H315 - Causes skin irritation. H332 - Harmful if inhaled. H411 - Toxic to aquatic life with long lasting effects.
CLP Precautionary statements	:	P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P331 - Do NOT induce vomiting P301+P310 - If swallowed, immediately call a doctor. P273 - Avoid release to the environment P405 - Store locked up
Contains	:	Distillates (petroleum), hydrotreated middle
WGK	:	2

16. OTHER INFORMATION

Text of R phrases mentioned in Section 3	:	R20 -Harmful by inhalation. R38 -Irritating to skin. R65 -Harmful: may cause lung damage if swallowed.
H-statements components	:	H304 -May be fatal if swallowed and enters airways. H315 -Causes skin irritation. H332 -Harmful if inhaled. H411 -Toxic to aquatic life with long lasting effects.
Sources of key data used to compile the datasheet	:	http://ecb.jrc.it 20100720 CONCAWE C&L update

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.